

Frommelt[®] SURVIVOR[™] 450S Dock Shelter

PART 1 - GENERAL

Page 1 of 2

- 1.1 CONDITIONS SPECIFIED ELSEWHERE: Section 010000 - General Requirements.
- 1.2 SUBMIT SHOP DRAWINGS showing overall dimensions (width, height).
- 1.3 SUBMIT 3 copies of manufacturer's owner's manual.
- 1.4 WARRANTY: Proposals submitted without the following written warranties will be considered non-responsive.
 - 1.4.1 Shelter manufacturer shall provide with his bid a written minimum 1-year parts and labor warranty, detailed specification sheet with sizes, projection, range of trucks to be serviced, and any other information necessary for proper installation and operation of the unit.
 - 1.4.2 Shelter parts not covered under the warranty shall include: NONE.
 - 1.4.3. In addition to all other warranties, the manufacturer shall warrant that the equipment will perform in a manner satisfactory to the Owner for a period of 12 months after date of installation. If Owner is not then satisfied with the performance of the equipment, the Owner may notify the manufacturer. Given that the points of dissatisfaction are bona fide and forwarded within the given time period, the manufacturer shall remove the equipment and refund the equipment purchase price to the Owner. This warranty shall be provided by the manufacturer in writing at time of bid.

PART 2 - PRODUCTS

- 2.1 Shelter shall be manufactured by **Rite-Hite** or an approved substitute. Shelter shall be sized by manufacturer to meet specific application requirements.
- 2.2 Shelter shall be 11' 3" overall width x _____' _____" overall height x _____" projection.
 - 2.2.1 Range of truck heights to be serviced shall be from _____' _____" to _____' _____".
- 2.3 Side curtains shall provide full access to trailer.
 - 2.3.1 Side frame shall be impactable, semi-rigid polyethylene frame with outer fabric covering, attached to treated lumber backer.
 - 2.3.2 Head curtain shall be constructed with five fiberglass stays.

2.3.3 Head curtain shall have fabric wear pleats on each end.

PART 2 - PRODUCTS (continued)

Page 2 of 2

2.3.4 Height of head curtain shall be 3” below height of normal lowest truck to be serviced.

2.3.5 Header shall be of fabric construction that diverts water off sides of header.

2.3.6 Side curtain & head curtain fabric shall be _____.

2.3.7 Collapsible draft pads shall seal the gap between the side frames and the sides of the trailer.

PART 3 - EXECUTION

3.1 INSTALLER shall examine the substrate and conditions under which shelter/seal is to be installed and notify the A/E and Contractor in writing of any conditions detrimental to the proper and timely completion of the work. Do not proceed with the work until unsatisfactory conditions have been corrected in a manner acceptable to the installer.

3.2 SHELTER/SEAL MANUFACTURER’S REPRESENTATIVE shall install shelter/seal in accordance with approved shop drawings and manufacturer’s recommendations.

3.3 AFTER INSTALLATION is completed, a representative of the manufacturer shall examine the installation and require that all adjustments necessary to assure proper operation of shelter/seal have been made. Before acceptance, an inspection shall be conducted in the presence of the Owner’s representative to guarantee that the shelter/seal operates properly in every respect.