



INSUL-RITE™ Sectional Doors

LOW HEADROOM SPECIFICATIONS



TORSION IN REAR



TORSION IN FRONT

CLEARANCE REQUIREMENTS

	2" Track	3" Track
Headroom Required Manual (Rear)	6"	6"
Headroom Required Manual (Front)	10" - 14½"*	10" - 14½"*
Headroom Req'd Trolley Oper. (Rear)	8½"	8½"
Headroom Req'd Trolley Oper. (Front)	12½" - 17"*	12½" - 17"*
Sideroom Required	6"	9"
Depth into Room Manual	OH** + 20"	OH + 20"
Depth into Room Trolley Operator	OH + 66"	OH + 66"

*Consult factory for exact measurement

**OH — Opening Height

GENERAL SPECIFICATIONS

Model Number: 5155/5255 SECTIONAL DOOR

SIZE:

Minimum: 4' x 6'
Maximum: 26' x 20'

PERIMETER SEALS:

Full perimeter seal of the opening on 5255 includes: section joint seals between sections, track-mounted side seal, vinyl top seal and flexible vinyl astragal on bottom edge. Top and side seals are optional on 5155.

TRACK:

16 gauge hot-dipped galvanized steel track available in 2" or 3". Track rollers are case-hardened inner steel races with 10-ball rollers.

SECTION DESIGN:

2" thick sections (5255), 1½" section (5155) constructed solid polyurethane foam core sandwiched between galvanized steel facings. Two-coat baked-on polyester finish with embossed pin-stripeing and a non-repeating stucco finish. Facings are roll-formed and separated with a thermal break to eliminate thermal conductance. Hot-dipped galvanized steel wrap-around end caps add strength, rigidity. CFC-11-free polyurethane foam with an R-value of 14.80 (5255) and 10.96 (5155). Optional insulated 24" x 6" lites available.

OPERATION:

Torsion spring counterbalance system with galvanized steel aircraft cable. Standard 10,000 cycle spring. Optional 25,000, 50,000 and 100,000 cycle springs available. Optional trolley-type motor operator.

WARRANTY:

Sections warranted for ten (10) years against cracking, splitting or deterioration due to rust-through, and seven (7) years against separation/degradation of foam insulation. Ten (10) years on insulation value.

Certified for construction:

By: _____

Job: _____

Date: _____

Location: _____

Company: _____

City: _____

Size: _____

State: _____

**RITE-HITE
DOORS**
The Leading Edge In Door Safety.

8900 North Arbon Drive
Milwaukee, WI 53223
Toll free 1-800-456-0600
1-414-355-2600
Fax: 1-414-355-9248
www.ritehite.com