

Rite-Hite® Dock Lighting



Functional Specifications

| | Flex Neck LED | HD-LED | Cool Head Incandescent |
|--|---------------|--------|------------------------|
| Dimmable Light Output | ✓ | | |
| Visual Indication of Light Intensity Setting | ✓ | | |
| Automatic Approach Dimming (reduces blinding) | ✓ | | |
| Power Save (reduces power consumption when idle) | ✓ | | |
| Warm Light (minimizes eye strain & photobiological risk) | ✓ | | ✓ |
| Low Profile Light Head (reduces chance of impact) | ✓ | | |
| Impact Resistant - No Glass | ✓ | ✓ | |
| Multi-Articulated Arm (allows infinite adjustment) | ✓ | | |
| Adjustable Arm Friction Joints (prevents sagging) | ✓ | | |
| Temperature Range of -5F to + 120F | ✓ | | ✓ |
| Corrosion Resistant - All Components & Hardware | ✓ | | |
| UL/cUL Listed & CE Certified | ✓ | ✓ | ✓ |

Technical Specifications

| | | | |
|--|---------|--------|------|
| Service Life (hours) | 175,200 | 50,000 | 1000 |
| Watts - Full Brightness | 18 | 18 | 150 |
| Watts - Half Brightness | 9 | N/A | N/A |
| Watts - Power Save ("night light" when idle) | 4 | N/A | N/A |
| Light Head Width (projection into trailer) | 2.75" | 6" | 6" |